

## Patent Abstracts of Japan

PUBLICATION NUMBER : 05259052  
PUBLICATION DATE : 08-10-93


APPLICATION DATE : 10-03-92  
APPLICATION NUMBER : 04051845

APPLICANT : KAWASAKI STEEL CORP;

INVENTOR : KUBO RYUJI;

INT.CL. : H01L 21/027 B05C 11/08 B05D 1/40  
G03F 7/16

TITLE : SPIN COATING ON SEMICONDUCTOR  
SUBSTRATE AND DEVICE



ABSTRACT : PURPOSE: To form a coating layer having no dead spot regardless of the presence or absence of a defect in the surface of a semiconductor substrate by a method wherein before a coating solution is dripped, a solvent is sprayed on the whole surface of the semiconductor substrate in a spray form.

CONSTITUTION: A solvent spray nozzle 7 is moved to the central part of a substrate 1 to position and a solvent is sprayed on the whole surface of the substrate 1 in a spray form through a funnel-shaped blow-off port 7. Then, after the nozzle 7 is moved aside to the side part of the substrate, a coating nozzle 4 is positioned to the central part of the substrate 1 and a coating solution 5 is dripped on the central part in a prescribed amount. After that, a rotating stage 2 is rotated in the direction indicated by arrow F at high speed via a spindle shaft 6 and the solution 5 is spread on the whole surface of the substrate 1. Thereby, regardless of the presence or absence of a defect in the surface of the substrate 1 a coating layer having no dead spot can be obtained and the quality and yield of the substrate can be improved.

COPYRIGHT: (C) JPO